



24-25 Stephenson Road,  
St Ives,  
Cambridgeshire,  
PE27 3WJ  
England.  
Tel: +44 (0)1480 494540  
Fax: +44 (0)1480 494206  
Email: info@lemark.co.uk  
Web: www.lemark.co.uk

## GEL-TAK FILTER FIX TAPE PRODUCT SPECIFICATION SHEET

### PRODUCT DESCRIPTION/ APPLICATION

Gel-Tak is a double-sided tape for filter where quality is paramount. It is extremely thin and highly transparent thus ensuring a clean and shadow-free mounting. It is UV light and age resistant and can be removed easily without leaving adhesive residues.

**Standard dimensions:** 12mm on 25m lengths (other sizes made to order)

### TECHNICAL DATA (Mean Values)

<b>Backing:</b>	Polyester PETP film
<b>Colour:</b>	Transparent
<b>Thickness*:</b>	0.03mm (without liner)
<b>Liner:</b>	Flat white silicone paper
<b>Adhesive:</b>	Acrylic
<b>Adhesion Steel/Glass*:</b>	7 N/25mm
<b>Continuous Performance Temperature:</b>	80°C (175°F)
<b>Short Term Temperature Resistance:</b>	200°C (400°F)

\*Parameters of the specification

### IMPORTANT

This information is based on our best current knowledge and is intended as a general guide to product performance. It is not a warranty or specification and customers must determine that the product is suitable for their particular purpose before use.

