

DP6

1-Channel 6kW

Studio Dimmer

The DP6 studio dimmer is designed to fulfil all the requirements of most lighting applications – mainly in TV or special venues, where single channel dimming by various controlling ways is needed. DP6 is equipped with 400us rise-time choke that guarantees very low lamp noise.

Another benefit of the DP6 is an option to use the W-DMX inside, which allows controlling the device without a DMX cable. Additionally, the DMX OUT connector serves as a source of the DMX signal for any other DMX equipment or colour changer.

Power supply

AC230V / 40-65Hz, single phase

Operating temperature

-20 °C to +40 °C

Housing

Aluminium; gray powder coating

Dimensions & Weight

270 x 220 x 360mm, 9.7kg

Warranty

5 years



DP6 features:

- Convectional cooling without fan
- WDMX / DMX / Fader control
- Power output: 1x 26A / 6W
- Main switch: 1x D32A
- Studio Rise-time: 400us
- DMX address selector
- LTP function fader/DMX
- DMX input with true output
- W-DMX with DMX output function
- Phase-angle control SSR
- Double over-heat protection
- Variable input/output connectors
- Type of connector: CEE32A/3p

DMX/W-DMX input with true output:

USITT DMX 512

Min. load:

100W

Max. load:

6000W

DP6_en_datasheet_M055