



# UNCOATED TEXTILE TAPE

High quality viscose fabric tape in combination with a strong synthetic rubber-based adhesive.

## Construction

<b>Adhesive</b>	Synthetic rubber
<b>Carrier</b>	Viscose fabric Black

## Applications

Cable bandaging. A smooth and durable flexible cable harness will be obtained by overlapping bandaging as well as by spiral bandaging.

Various applications in veterinary medicine for bandaging large and small animals.

For taping ice hockey sticks.

Bundling of strips, rods and cables.

Strengthening book jackets.

## Technical details

<b>Thickness</b>	0,30 mm
<b>Adhesive strength</b>	12,5 N/25 mm
<b>Tensile strength</b>	200 N/25 mm
<b>Service temperature range</b>	-40°C to +105°C

## Recommendations for use

Temperature: between +20°C and +24°C. Surface must be clean and free from dust and grease. Avoid touching exposed adhesive surface of the tape, as this impairs the performance. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24HRS at +23°C.

## Storage and shelf life

Clean and dry in a well ventilated area, preferably at a temperature between +10°C and +30°C. Stored under these conditions shelf life will be a minimum of 24 months.

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Option Tape Specialties cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.



### OPTION TAPE SPECIALTIES

Frankrijkstraat 8 - Zone Waas number 2529

9140 Temse - Belgium

Tel. : +32 (0)3 710 19 19 - Fax : +32 (0)3 711 34 64

info@optiontapespecialties.com - www.optiontapespecialties.com

Last version 18/10/2022