



No. 1 Houghton Hill Industries  
 Sawtry Way  
 Houghton, Huntingdon,  
 Cambridgeshire  
 PE28 2DH  
 England  
 Tel: +44 (0)1480 494540  
 Fax: +44 (0)1480 494206  
 Email: [Info@lemark.co.uk](mailto:Info@lemark.co.uk)  
 Web: [www.lemark.co.uk](http://www.lemark.co.uk)

## MAGTAPE® Back 2 Black

Product Information  
 Technical Specification

Carrier	PE Coated Cloth
Adhesive-Base	Rubber
Total Thickness ( MM )	0.31
Peel Adhesion ( Kg/25mm )	0.9
Rewinding Force ( Kg/50mm )	2
Tensile Strength ( Kg/25mm )	16
Holding Power (25mm x 25mm / 40°C )	60 min
Ball Tack ( CM / Ball no. 20 )	10
Temperature Resistance 1h / °C	-35 / up to +80
Storage Life ( 20°C / 60% )	6 months

The used test methods are based on acceptable specifications like PTSC or internal test methods which are required on request.

### Remark:

All the technical data are average values and should not be regarded as MAXIMUM or MINIMUM values for specification purposes. We advise to test the material required to ensure the suitability of intended application.

### Storage:

Tapes stored below the minimum application temperature will require warming up to the level before. Up to 24 hours may be required for this to take place.

### Product Design

